

## Gasket Materials

### **CN-705**

#### **Description**

CN-705 is a low-density, nitrile butadiene bound material that is suitable for use with oil, gasoline, and water. It is intended for use in applications with short duration maximum temperatures up to 180°C (350°F).

### **CMP-4000**

#### **Description**

CMP-4000 is a high performance, compressed MicroPore material, combining a unique synthetic fiber matrix and fully cured nitrile butadiene rubber binder. It has excellent sealability and torque retention properties and is recommended for OEM and Industrial applications with short duration maximum temperatures up to 350°C (650°F).

### **TN-9000**

#### **Description**

TN-9000 has a fully cured nitrile butadiene binder with Aramid fiber. It has good tensile strength, low creep relaxation, and excellent fuel and oil resistance. It is intended for applications with high flange pressures and temperatures, with short duration maximum temperatures up to 400°C (750°F).

### **CS-301**

#### **Description**

CS-301 has a controlled-swell styrene butadiene rubber binder. It is intended for use in applications with water, high aniline point oil, and other applications not including aromatic fuels and certain solvents, and with short duration maximum temperatures up to 180°C (350°F).

### **2331**

#### **Description**

2331 is an environmentally compatible, low density gasket material formulated from recycled gasket materials. It has added styrene butadiene rubber binder, and is intended for general, light-duty applications with short duration maximum temperatures up to 180°C (350°F).

### **SV-360**

#### **Description**

SV-360 is a low density cellulose fiber material with styrene butadiene rubber binder. It is a general purpose material for anti-squeak, dust seals, heaters, oil seals, shim stock, and water pumps. It is intended for applications with short duration maximum temperatures up to 180°C (350°F).